



Hybrid Extreme NVR (SD + IP)



Model Specifications

Model		HX-2408	HX-48016	HX-96032
SD Video Input	Total Channels	8 BNC	16 BNC	32 BNC
	SD Format	SD (Analog), 1Vp/p, 75Ohm		
		30 ips each Channel Record and Display @ 720x480 (Full D1)		
Audio	Input	8	16	32
	Output	1	1	1
Alarm Input	TTL input	8 or 16 (Optional)		
Alarm Output	Relay out	8 or 16 (Optional)		
PTZ Port		1 (Optional)		
Spot out		2 (Optional) to Analog	2 (Optional)	2 (Optional)
SD Display & Record	Output	1xVGA and 1xHDMI or 1xVGA and 1xDVI		
	Format	H.264 H/W Compression		
	Mode	Continuous, Motion, Event, Key-frame, Customize		
	Images per Second	240ips @ 720x480 (Full D1)	480ips @ 720x480 (Full D1)	960ips @ 720x480 (Full D1)
IP Cameras (Optional)	Video	Up to 32 IP Channels	Up to 32 IP Channels	Up to 32 IP Channels
	Format	H.264 S/W Compression		
	Resolution	1080p (1920x1080) / 720p (1280x720) / D1 (720x480)		
IP Camera Display & Record	Megapixel	Up to 480 ips	Up to 480 ips	Up to 480 ips
	Mode	Continuous, Motion, Event, Key-frame, Customize		
	Quality	Selectable by Kbps rate		
Software	Search Mode	Calendar, Time line, Thumbnail, Event, Smart, Bookmark		
	Archive	JPEG, PNG, AVI format		
		CD/DVD Burn, USB, Local Hard drive		
Display	PTZ Control, Digital Zoom, Listen Audio, Output Trigger Control			
General	VGA	Intel HD Graphics 4000		
	Network	1 Gb per second		
	OS	Windows 7 Professional - 64 bit		
Case		Rack Mount (4U) or Tower Case		

Four Year Warranty

**Specifications subject to change without notice.*

(888) 421-0050 / www.cascadiadvrt.com